



LIGHTS

Speaks Safety & Quality

Product Catalogue




GROUP

Total Power Solution

Head Office

Suvastu Suraiya Trade Center, Level: 9-13, Plot: 57, Road: 21, Block: B,
Kemal Ataturk Avenue, Banani, Dhaka-1213, Bangladesh.
Hotline: 01755-661166, Web: www.sqgroup.com



EMERGENCY LIGHTS

| | |
|----------------------------------|-------------------------------|
| Brand | : SQ LED Lights |
| Model | : A60-6W Emergency Light |
| Input Voltage | : 100-285V AC |
| Input Power | : 6W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : 105lm/W $\pm 5\%$ |
| Luminous Flux | : 590lm $\pm 5\%$ |
| CRI | : ≥ 80 |
| Beam Angle | : 270° |
| Battery Type | : High Quality Li-Ion Battery |
| Battery Backup Time | : 2-3hrs |
| Battery Charging Time | : >8hrs |
| Turn on Delay (S) | : N/A |
| Life Time (Hrs.) | : 20000hrs |
| Dimension | : $\phi 60 \times 126$ |
| Luminous Flux on Emergency State | : 240lm |

6 W



8 W

EMERGENCY LIGHTS

| | |
|----------------------------------|-------------------------------|
| Brand | : SQ LED Lights |
| Model | : A60-8W Emergency Light |
| Input Voltage | : 100-285V AC |
| Input Power: 6W | : 8W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : 110lm/W $\pm 5\%$ |
| Luminous Flux | : 830lm $\pm 5\%$ |
| CRI | : ≥ 80 |
| Beam Angle | : 270° |
| Battery Type | : High Quality Li-Ion Battery |
| Battery Backup Time | : 2-3hrs |
| Battery Charging Time | : >8hrs |
| Turn on Delay (S) | : N/A |
| Life Time (Hrs.) | : 20000hrs |
| Dimension | : $\phi 60 \times 126$ |
| Luminous Flux on Emergency State | : 320lm |

EMERGENCY LIGHTS

| | |
|----------------------------------|-------------------------------|
| Brand | : SQ LED Lights |
| Model | : A60-10W Emergency Light |
| Input Voltage | : 100-285V AC |
| Input Power: 6W | : 10W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : 115lm/W $\pm 5\%$ |
| Luminous Flux | : 1150lm $\pm 5\%$ |
| CRI | : ≥ 80 |
| Beam Angle | : 270° |
| Battery Type | : High Quality Li-Ion Battery |
| Battery Backup Time | : 2-3hrs |
| Battery Charging Time | : >8hrs |
| Turn on Delay (S) | : N/A |
| Life Time (Hrs.) | : 20000hrs |
| Dimension | : $\phi 60 \times 126$ |
| Luminous Flux on Emergency State | : 320lm |

10 W



LED BULB

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V AC |
| Input Power | : 3W |
| Frequency | : 50-60 Hz |
| Power Factor | : ≥ 0.5 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 270lm |
| CRI | : ≥ 80 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

3 W

LED BULB

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V AC |
| Input Power | : 5W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.5 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 450lm |
| CRI | : ≥ 80 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

5 W

LED BULB

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V AC |
| Input Power | : 7W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.5 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 630lm |
| CRI | : ≥ 80 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

7 W

LED BULB

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V AC |
| Input Power | : 9W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.5 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 810lm |
| CRI | : ≥ 80 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

9 W

LED BULB

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V AC |
| Input Power | : 12W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.5 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 1080lm |
| CRI | : ≥ 80 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

12 W

LED BULB

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V AC |
| Input Power | : 15W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.5 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 1350lm |
| CRI | : ≥ 80 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

15 W

SQ



LED Lamp (T-Shape)

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90 -270V Ac |
| Input Power | : 20W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 1800lm |
| CRI | : ≥ 85 |
| THD | : <15% |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

20 W

LED Lamp (T-Shape)

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V Ac |
| Input Power | : 30W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 2700lm |
| CRI | : ≥ 85 |
| THD | : < 15% |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

30 W

LED Lamp (T-Shape)

| | |
|---------------------|-----------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V Ac |
| Input Power | : 40W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Output | : 3600lm |
| CRI | : ≥ 85 |
| THD | : < 15% |
| Turn on Instantly | : Yes |
| Hazardous Materials | : B22/E27 |
| Lamp Cap | : No |
| Lifetime | : 30000Hrs |

40 W

LED Lamp (T-Shape)

| | |
|---------------------|--------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V Ac |
| Input Power | : 50W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Output | : 4500lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

50 W

LED Lamp (T-Shape)

| | |
|---------------------|--------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V Ac |
| Input Power | : 65W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Output | : 5850lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

65 W

LED Lamp (T-Shape)

| | |
|---------------------|--------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 90-270V Ac |
| Input Power | : 85W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Output | : 7650lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lamp Cap | : B22/E27 |
| Lifetime | : 30000Hrs |

85 W



LED Flood Light (SQ-TJC)

| | |
|--|---------------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 100-260V AC |
| Input Power | : 20W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 20W LED |
| LED Quantity | : 20WX1 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 1800lm |
| CRI | : ≥ 85 |
| Beam Angle | : $105^\circ - 120^\circ$ |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 30000Hrs |
| Housing: High Conductive Aluminum alloy Radiator | |

20 W



LED Flood Light (SQ-TJC)

| | |
|--|---------------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 100-260V AC |
| Input Power | : 30W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 30W LED |
| LED Quantity | : 30WX1 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 2700lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Beam Angle | : $105^\circ - 120^\circ$ |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 30000Hrs |
| Housing: High Conductive Aluminum alloy Radiator | |

30 W



LED Flood Light (SQ-TJC)

| | |
|--|---------------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 100-260V AC |
| Input Power | : 50W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 50W LED |
| LED Quantity | : 50WX1 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 4500lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Beam Angle | : $105^\circ - 120^\circ$ |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 30000Hrs |
| Housing: High Conductive Aluminum alloy Radiator | |

50 W



LED Flood Light (SQ-TJC)

| | |
|--|---------------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 100-260V AC |
| Input Power | : 100W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 100W LED |
| LED Quantity | : 50WX2 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 9000lm |
| CRI | : ≥ 85 |
| Beam Angle | : $105^\circ - 120^\circ$ |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 30000Hrs |
| Housing: High Conductive Aluminum alloy Radiator | |

100 W



LED Flood Light (SQ-TJC)

| | |
|--|---------------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 100-260V AC |
| Input Power | : 150W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 150W LED |
| LED Quantity | : 50WX3 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 13500lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Beam Angle | : $105^\circ - 120^\circ$ |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 30000Hrs |
| Housing: High Conductive Aluminum alloy Radiator | |


150 W



LED Flood Light (SQ-TJC)

| | |
|--|---------------------------|
| Brand | : SQ LED Lights |
| Input Voltage | : 100-260V AC |
| Input Power | : 200W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 200W LED |
| LED Quantity | : 50WX4 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 18000lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Beam Angle | : $105^\circ - 120^\circ$ |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 30000Hrs |
| Housing: High Conductive Aluminum alloy Radiator | |


200 W



LED Flood Light (SQ-SMD)

| | |
|-----------------|---|
| Brand. | : SQ LED Lights |
| Model No. | : Flood-20W-16A |
| Input Voltage | : 100-260V Ac |
| Input Power | : 20W |
| Frequency | : 50 Hz |
| Light Source | : SMD Integrated High Quality LED's |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 1800lm |
| CRI | : ≥ 80 |
| THD | : $< 15\%$ |
| Beam Angle | : 120° |
| On/Off | : >15000 |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 25000Hrs |
| Housing: | High Conductive Aluminum alloy Radiator |


20 W



LED Flood Light (SQ-SMD)

| | |
|-----------------|---|
| Brand. | : SQ LED Lights |
| Model No. | : Flood-30W-16A |
| Input Voltage | : 100-260V Ac |
| Input Power | : 30W |
| Frequency | : 50 Hz |
| Light Source | : SMD Integrated High Quality LED's |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 2700lm |
| CRI | : ≥ 80 |
| THD | : $< 15\%$ |
| Beam Angle | : 120° |
| On/Off | : >15000 |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 25000Hrs |
| Housing: | High Conductive Aluminum alloy Radiator |


30 W



LED Flood Light (SQ-SMD)

| | |
|-----------------|---|
| Brand. | : SQ LED Lights |
| Model No. | : Flood-50W-16A |
| Input Voltage | : 100-260V Ac |
| Input Power | : 50W |
| Frequency | : 50 Hz |
| Light Source | : SMD Integrated High Quality LED's |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 4500lm |
| CRI | : ≥ 80 |
| THD | : $< 15\%$ |
| Beam Angle | : 120° |
| On/Off | : >15000 |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 25000Hrs |
| Housing: | High Conductive Aluminum alloy Radiator |


50 W



LED Flood Light (SQ-SMD)

| | |
|-----------------|---|
| Brand. | : SQ LED Lights |
| Model No. | : Flood-100W-16A |
| Input Voltage | : 100-260V Ac |
| Input Power | : 100W |
| Frequency | : 50 Hz |
| Light Source | : SMD Integrated High Quality LED's |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Flux | : 9000lm |
| CRI | : ≥ 80 |
| THD | : < 15% |
| Beam Angle | : 120° |
| On/Off | : >15000 |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 25000Hrs |
| Housing | : High Conductive Aluminum alloy Radiator |


100 W



LED Flood Light (SQ-SMD)

| | |
|-----------------|---|
| Brand. | : SQ LED Lights |
| Model No. | : Flood-150W-16A |
| Input Voltage | : 100-260V Ac |
| Input Power | : 150W |
| Frequency | : 50 Hz |
| Light Source | : SMD Integrated High Quality LED's |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Flux | : 13500lm |
| CRI | : ≥ 80 |
| THD | : < 15% |
| Beam Angle | : 120° |
| On/Off | : >15000 |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 25000Hrs |
| Housing | : High Conductive Aluminum alloy Radiator |


150 W



LED Flood Light (SQ-SMD)

| | |
|-----------------|---|
| Brand. | : SQ LED Lights |
| Model No. | : Flood-200W-16A |
| Input Voltage | : 100-260V Ac |
| Input Power | : 200W |
| Frequency | : 50 Hz |
| Light Source | : SMD Integrated High Quality LED's |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : >90lm/W |
| Luminous Flux | : 18000lm |
| CRI | : ≥ 80 |
| THD | : < 15% |
| Beam Angle | : 120° |
| On/Off | : >15000 |
| Dimension | : |
| G.W/N.W | : |
| Lifetime | : 25000Hrs |
| Housing | : High Conductive Aluminum alloy Radiator |

200 W



LED Panel Light

| | |
|--|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 90-265V AC |
| Input Power | : 3W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 6500K |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Output | : 270lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Available Model: Slim Round, Slim Square, Surface Round, Surface Square. | |

3 W



LED Panel Light

| | |
|--|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 90-265V AC |
| Input Power | : 6W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 2700K/6500K/M |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Output | : 540lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Available Model: Slim Round, Slim Square, Surface Round, Surface Square. | |

6 W



LED Panel Light

| | |
|--|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 90-265V AC |
| Input Power | : 9W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 2700K/6500K/M |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Output | : 810lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Available Model: Slim Round, Slim Square, Surface Round, Surface Square. | |

9 W



LED Panel Light

| | |
|--|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 90-265V AC |
| Input Power | : 12W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 6500K |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Output | : 1080lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Available Model: Slim Round, Slim Square, Surface Round, Surface Square. | |

12 W



LED Panel Light

| | |
|--|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 90-265V AC |
| Input Power | : 15W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 2700K/6500K/M |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Output | : 1350lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Available Model: Slim Round, Slim Square, Surface Round, Surface Square. | |

15 W



LED Panel Light

| | |
|--|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 90-265V AC |
| Input Power | : 18W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 6500K/M |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Output | : 1620lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Available Model: Slim Round, Slim Square, Surface Round, Surface Square. | |

18 W



LED Panel Light

| | |
|--|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 90-265V AC |
| Input Power | : 24W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 2700K/6500K/MC |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Output | : 2160lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Available Model: Slim Round, Slim Square, Surface Round, Surface Square. | |

24 W



LED Tube Light (T-8)

| | |
|---------------------|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 100-265V AC |
| Input Power | : 10W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 6500M |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Flux | : 900lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Dimension | : 2' (Feet) |

10 W



LED Tube Light (T-8)

| | |
|---------------------|---------------------|
| Brand. | : SQ LED Lights |
| Input Voltage | : 100-265V AC |
| Input Power | : 20W |
| Frequency | : 50 Hz |
| Power Factor | : ≥ 0.9 |
| Available CCT | : 6500M |
| Efficacy (lm/W) | : $> 90\text{lm/W}$ |
| Luminous Flux | : 1800lm |
| CRI | : ≥ 85 |
| Turn on Instantly | : Yes |
| Hazardous Materials | : No |
| Lifetime | : 30000Hrs |
| Dimension | : 4' (Feet) |

20 W



LED Street Light

| | |
|---|--------------------------|
| Brand. | : SQ LED Lights |
| Model | : LED-100W |
| Input Voltage | : 100-260V AC |
| Input Power | : 100W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 50W LED |
| LED Quantity | : 50W X 2 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 9000lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Dimension | : 70X28X11cm |
| G.W/N.W | : 3.50/3.00KG |
| Lifetime | : 30000Hrs |
| Beam Angle: Horizontal - 120°, Vertical - 45° | |
| Housing: High Conductivity Aluminum Radiator | |

100 W

LED Street Light

| | |
|---|--------------------------|
| Brand. | : SQ LED Lights |
| Model | : LED-150W |
| Input Voltage | : 100-260V AC |
| Input Power | : 150W |
| Frequency | : 50 Hz |
| Light Source | : COB Integrated 50W LED |
| LED Quantity | : 50W X 3 |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>90\text{lm/W}$ |
| Luminous Flux | : 13500lm |
| CRI | : ≥ 85 |
| THD | : $< 15\%$ |
| Dimension | : 80X32X13cm |
| G.W/N.W | : 4.0/3.50KG |
| Lifetime | : 30000Hrs |
| Beam Angle: Horizontal - 120°, Vertical - 45° | |
| Housing: High Conductivity Aluminum Radiator | |

150 W

LED High Bay Light

| | |
|--|-------------------------------|
| Brand. | : SQ LED Lights |
| Model | : LED-150W |
| Input Voltage | : 170-260V AC |
| Input Power | : 150W |
| Frequency | : 50 Hz |
| Light Source | : 2835 1W Korea Semiconductor |
| LED Quantity | : 1W X 150Pcs |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>100\text{lm/W}$ |
| Luminous Flux | : 15000lm |
| CRI | : 85 |
| THD | : $< 15\%$ |
| Beam Angle: | : 45-65° |
| Cover Size | : 50X50X33cm |
| G.W/N.W | : 2.0/1.45KG |
| Lifetime | : 40000Hrs |
| Housing: High Conductivity Aluminum Radiator | |

150 W

LED High Bay Light

| | |
|--|-------------------------------|
| Brand. | : SQ LED Lights |
| Model | : LED-200W |
| Input Voltage | : 170-260V AC |
| Input Power | : 200W |
| Frequency | : 50 Hz |
| Light Source | : 2835 1W Korea Semiconductor |
| LED Quantity | : 1W X 200Pcs |
| Power Factor | : ≥ 0.9 |
| CCT | : 6500K |
| Efficacy (lm/W) | : $>100\text{lm/W}$ |
| Luminous Flux | : 20000lm |
| CRI | : 85 |
| THD | : $< 15\%$ |
| Beam Angle: | : 45-65° |
| Cover Size | : 50X50X35cm |
| G.W/N.W | : 2.0/1.45KG |
| Lifetime | : 40000Hrs |
| Housing: High Conductivity Aluminum Radiator | |

200 W



LED Down Light

| | |
|--------------|-----------------|
| Model | : Flood-30W-16A |
| Watts | : 30W |
| Lumen | : 2700lm |
| CRI | : ≥ 80 |
| Power Factor | : 0.9 |
| Lifetime | : 25000h |
| On/Off | : 15000 |
| Angel | : 120° |

30 W

